



TURMOCUT SR 68



Date of issue: 03.08.2017

TURMOCUT SR 68 is a foodgrade cutting-, cleaning- and conservation oil based on high purity hydrocarbons. It is used in the paper- and corrugating industry.

TURMOCUT SR 68 is InS/H1 approved as lubricant for which an incidental contact with food technically cannot be avoided.

Special properties

- Excellent corrosion and wear protection
- Excellent lubricating properties
- Very good surface wetting abilities
- Guarantees an optimum felt penetration
- Excellent dissolving effects of starch residues

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellowish, transparent		
Density at 20°C	0,87	g/cm ³	DIN 51757
Operating temperature range	-10 to 160	°C	
Oil type	high purity hydrocarbons		
Kinematic viscosity at 40°C	68,3	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	10,2	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	133		DIN ISO 2909
Pour point	-12	°C	DIN ISO 3016
Flash point	> 200	°C	DIN EN ISO 2592

Application

TURMOCUT SR 68 is used for lubricating, cleaning and conservation of the slitter scorer.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



1796858



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>