



TURMOFLUID 680



Date of issue: 18.09.2018

TURMOFLUID 680 is a multipurpose oil based on mineral oil.

Special properties

- Good adhesive properties
- Good wear protection
- Good corrosion protection
- High load carrying capacity
- Not emulsifying so it is good dissoluble in treatment processes
- No corrosion of nonferrous metals up to 100°C

Product Characteristics	Value	Dimension	Norm / Standard
Colour	yellow		
Density at 20°C	0,9	g/cm ³	DIN 51757
Operating temperature range	-5 to 120	°C	
Oil type	Mineral oil		
Kinematic viscosity at 40°C	680	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	40	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	98		DIN ISO 2909
Pour point	-10	°C	DIN ISO 3016
Flash point	> 250	°C	DIN EN ISO 2592
Copper corrosion category 24 h / 100°C	1a		DIN EN 2160

Application

TURMOFLUID 680 is used as lubricating oil, chain or gear oil in diverse industrial areas.

Packaging units

20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>