



TURMOFLUID HLP 10



Date of issue: 07.03.2018

TURMOFLUID HLP 10 is an optimized hydraulic oil based on mineral oil.

TURMOFLUID HLP 10 meets the HLP requirements according DIN 51024.

Special properties

- High level of performance
- High ageing resistance
- Very good high load carrying capacity
- Excellent wear protection
- Very good corrosion protection

Product Characteristics	Value	Dimension	Norm / Standard
Colour	brownish, transparent		
Density at 20°C	0,842	g/cm ³	DIN 51757
Oil type	Mineral oil		
Kinematic viscosity at 40°C	10	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	2,7	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	108		DIN ISO 2909
Pour point	-32	°C	DIN ISO 3016
Flash point	> 160	°C	DIN EN ISO 2592

Application

TURMOFLUID HLP 10 is used as pressure fluid in hydraulic systems of the entire industry.

Packaging units

6 x 1 l bottles, 6 x 5 l canisters, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>