



## TURMOFLUID HLP 32 multi



Date of issue: 23.05.2019

**TURMOFLUID HLP 32 multi** is an optimized HVI hydraulic oil based on mineral oil.

**TURMOFLUID HLP 32 multi** meets the HLP requirements according DIN 51524.

### Special properties

- High level of performance
- Very good viscosity-temperature behaviour
- High ageing resistance
- Very good high load carrying capacity
- Excellent corrosion and wear protection
- Neutral towards most sealing materials

| Product Characteristics      | Value        | Dimension          | Norm / Standard |
|------------------------------|--------------|--------------------|-----------------|
| Colour                       | light yellow |                    |                 |
| Density at 20°C              | 0,87         | g/cm <sup>3</sup>  | DIN 51757       |
| Oil type                     | Mineral oil  |                    |                 |
| Kinematic viscosity at 40°C  | 32           | mm <sup>2</sup> /s | DIN EN ISO 3104 |
| Kinematic viscosity at 100°C | 6,0          | mm <sup>2</sup> /s | DIN EN ISO 3104 |
| Viscosity index (VI)         | 136          |                    | DIN ISO 2909    |
| Pour point                   | ≤ -25        | °C                 | DIN ISO 3016    |
| Flash point                  | > 180        | °C                 | DIN EN ISO 2592 |

### Application

**TURMOFLUID HLP 32 multi** is used as pressure fluid in hydraulic systems of the entire industry.

### Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>