



TURMOFLUID HLPD 15



Date of issue: 01.11.2018

TURMOFLUID HLPD 15 is a hydraulic oil according to DIN 51524. It has an optimized additive composition and for this reason it ensures a high operating efficiency. Selected additives make it possible to absorb a certain amount of water without clouding the oil.

Special properties

- Excellent high load carrying capacity
- Excellent corrosion and wear protection
- Very good viscosity-temperature behaviour
- Very high ageing stability
- Optimum dispersing properties
- Excellent detergency
- Low foaming tendency

| Product Characteristics | Value | Dimension | Norm / Standard |
|------------------------------|------------------------|--------------------|-----------------|
| Colour | yellowish, transparent | | |
| Density at 20°C | 0,86 | g/cm ³ | DIN 51757 |
| Oil type | Mineral oil | | |
| Kinematic viscosity at 40°C | 15 | mm ² /s | DIN EN ISO 3104 |
| Kinematic viscosity at 100°C | 3,5 | mm ² /s | DIN EN ISO 3104 |
| Viscosity index (VI) | 112 | | DIN ISO 2909 |
| Pour point | < -25 | °C | DIN ISO 3016 |
| Flash point | > 170 | °C | DIN EN ISO 2592 |

Application

TURMOFLUID HLPD 15 is mainly applied in machines, hydraulic systems and other areas with condensed water.

Packaging units

60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>