



# TURMOGEOIL 460 OM



Date of issue: 06.02.2019

**TURMOGEOIL 460 OM** is a gear oil for high loads and extended oil change intervals.

**TURMOGEOIL 460 OM** contains a combination of special additives which smoothen the contact surface of gear wheels, even if damages caused by conventional gear oil have already occurred.

**TURMOGEOIL 460 OM** meets the CLP requirements of DIN 51517.

## Special properties

- High load carrying capacity
- Excellent wear protection
- High ageing resistance
- Low foaming tendency
- Not emulsifying
- Neutral to sleeves and most sealing material
- No corrosion of nonferrous metals up to 100°C
- Long oil change intervals, low maintenance costs

Product Characteristics	Value	Dimension	Norm / Standard
Colour	brownish / transparent		
Density at 20°C	0,89	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-5 to 100	°C	
Oil type	Mineral oil		
Kinematic viscosity at 40°C	460	mm <sup>2</sup> /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	29	mm <sup>2</sup> /s	DIN EN ISO 3104
Viscosity index (VI)	90		DIN ISO 2909
Pour point	≤ -10	°C	DIN ISO 3016
Flash point	> 220	°C	DIN EN ISO 2592

## Application

**TURMOGEOIL 460 OM** is used for the lubrication of gear drives and bearings with splash or oil circulation as well as for claw couplings, pressure-bearings of roller journals and high loaded joints. The oil is especially suitable for gears and bearings of roller plant frames, calendar, mine-machines, winches and crushing machines and gearboxes in textile machinery e. g. weaving machines.

## Note

The most gearbox housings are usually equipped with a protective interior coating. The used coatings are commonly resistant against gear oils based on mineral oil only up to 100°C.

This may cause the coatings to dissolve at temperatures above 100°C and lead to gear damage.

Therefore, the use of **TURMOGEOIL 460 OM** at higher temperatures needs to be tested on a case-by-case basis.

## Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>