



TURMOGAROIL CLP 100 EP



Date of issue: 30.04.2019

TURMOGAROIL CLP 100 EP is a gear oil for high loads and extended oil change intervals.

TURMOGAROIL CLP 100 EP meets the CLP requirements of DIN 51517.

Special properties

- High load carrying capacity
- Very good corrosion protection
- High ageing resistance
- Low foaming tendency
- Not emulsifying
- Neutral to sleeves and most sealing material
- No corrosion of nonferrous metals up to 100°C

Product Characteristics	Value	Dimension	Norm / Standard
Colour	red brown, clear		
Density at 20°C	0,88	g/cm ³	DIN 51757
Operating temperature range	to 120	°C	
Oil type	Mineral oil		
Kinematic viscosity at 40°C	100	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	11	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	94		DIN ISO 2909
Pour point	≤ -5	°C	DIN ISO 3016
Flash point	> 230	°C	DIN EN ISO 2592

Application

TURMOGAROIL CLP 100 EP is used for the lubrication of gear drives and bearings with splash or oil circulation as well as for claw couplings, pressure-bearings of roller journals and high loaded joints. The oil is especially suitable for gears and bearings of roller plant frames, calendar, mine-machines, winches and crushing machines and gearboxes in textile machinery e. g. weaving machines.

Note

The most gearbox housings are usually equipped with a protective interior coating. The used coatings are commonly resistant against gear oils based on mineral oil only up to 100°C.

This may cause the coatings to dissolve at temperatures above 100°C and lead to gear damage.

Therefore, the use of **TURMOGAROIL CLP 100 EP** at higher temperatures needs to be tested on a case-by-case basis.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>